




**Hearth Products Controls Co**  
**EVOLUTION 360 WATER PIT SERIES**  
**CSA CERTIFIED-OUTDOOR USE ONLY**  
**FOR COMMERCIAL AND RESIDENTIAL USE**

HEARTH PRODUCTS CONTROLS  
3050 PLAINFIELD RD.  
KETTERING, OH 45432  
TOLL FREE: 1-877-433-7001  
PHONE: (937) 433-7000  
FAX: (937) 433-0704  
www.hpcfire.com



WATER PIT WITH WATER FEATURE

Includes Basin, 26" Copper Water Bowl fitted with Certified Electronic Ignition Fit Pit and Lava Rock

| PART NUMBER     | DESCRIPTION                    |
|-----------------|--------------------------------|
| WB52R-TEMP4-EI  | 4-SCUPPER FEATURE - 90K BTU    |
| WB52-TEMP360-EI | 360° SCUPPER FEATURE - 90K BTU |

WATER PIT WITH OPTIONAL FIRE PIT




Includes Basin and 26" Copper Planter

| PART NUMBER  | DESCRIPTION                     |
|--------------|---------------------------------|
| WB52R-TEMP4  | 4-SCUPPER FEATURE WATER BOWL    |
| WB52-TEMP360 | 360° SCUPPER FEATURE WATER BOWL |

VISIT [www.hpcfire.com](http://www.hpcfire.com) FOR OTHER WATER FEATURE OPTIONS FEATURES:  
WATER ROCK - 3 BAGS REQUIRED

| MODEL #  | ROCK COLOR | SIZE | WEIGHT/BAG |
|----------|------------|------|------------|
| 957-BLK  | BLACK      | 2-4" | 55LBS      |
| 957-TAN  | TAN        | 2-4" | 55LBS      |
| 957-RED  | RED        | 2-4" | 55LBS      |
| 957-GREY | GREY       | 2-4" | 55LBS      |

- OPTIONAL FIRE FEATURE
- LOW LEVEL PUMP PROTECTION
- AUTO REFILL
- OVERFLOW
- DRAIN
- LED LIGHTS
- ADJUSTABLE WATER FLOW
- ADJUSTABLE HEIGHT WITH LEVELING LEGS
- NEMA RATED ELECTRICAL SYSTEM
- WATER FILTER




ISOMETRIC VIEW

Notes:

1. PROPER VENTING
  - ENCLOSURES: Recommend 4 each 18 sq.in. vents on opposing sides (Minimum 2 each 18 sq.in. vents).
  - BOWLS (Copper, concrete or metal) - Bowl to be raised above mounting surface minimum of 3/4" gap;  
Bowl to have a minimum of 6" diameter hole in bottom
2. GAS SUPPLY - FOR USE WITH FIXED PIPING SYSTEMS ONLY - NOT FOR USE WITH SMALL TANKS.
  - Natural Gas: Operating Supply Pressure: Minimum: 6.0" W.C.; Maximum: 7.0" W.C.
  - LP Gas: Operating Supply Pressure: Minimum: 10.0" W.C.; Maximum: 11.0" W.C.

IMPORTANT: Ensure any flex line that may be used from the permanent main fuel supply to the product is rated to the stated max btu of the product and certified to ANSI Z21.75\*CSA 6.27.

5. MODIFICATION OF PRODUCT WILL VOID ANY CERTIFICATION AND WARRANTY.
6. FOLLOW ALL MANUFACTURER INSTALLATION INSTRUCTIONS AND LOCAL CODES.
7. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS AS OF THE REVISION DATE.
8. DO NOT SCALE DRAWING.
9. THESE DRAWINGS ARE FOR SIZING AND PLANNING PURPOSES. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT. THE MANUFACTURER'S RESPONSIBLE FOR THE ACCURACY OF THE DRAWING.
10. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info)  
REFERENCE NUMBER 771-049.



EVOLUTION 360 - PLUG-N-PLAY WATER SYSTEM  
OPTIONAL CSA CERTIFIED FIRE PIT INSERT